



Demand more. Choose Foster

EP13L

Eco Pro G2 1/3 Freezer Counter



Temperature



Freezer
-18/-21 C

Dimensions (mm)

W 1865 D 700
H 865

Capacity

undefined Litres

Features & Benefits

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

Supplied as Standard Optional Not Available Yes No **P** Information Pending

External Finish

304 Stainless Steel

304 Stainless Steel Rear For Island Siting

Internal Finish

304 Stainless Steel

Aluminium

Shelving

Additional Shelf

Nylon Coated Gastronorm 1/1 Shelf Quantity: 6

Worktop & Drawers

Worktop

100mm Splashback

Less Worktop

Doors

Solid Full

Base Fittings

80mm Castors

150mm Legs

Levelling Bolts

Refrigeration

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input type="radio"/>
R404a	<input checked="" type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

Electrical Data & Service Information

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R404a)	10.2
Test Standard	PR EN153
Source	Laboratory Test
Watts	P
Fuse Required	13 amp

Product Extras

Helicoil Mains Lead	<input type="radio"/>
Marine Kit	<input type="radio"/>
Width Reduction (178mm reduction available when remote option selected)	<input type="radio"/>

Foot Notes

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit

- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm

Contact

Foster Refrigerator

Oldmedow Road
 King's Lynn
 Norfolk
 PE30 4JU
 United Kingdom

Telephone: **0843 216 8800**

Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE