



Demand more. Choose Foster

EP1440H

EcoPro G2 1350 Litre Upright Refrigerated Cabinet




Temperature



Refrigerator
+1/+4 C

Dimensions (mm)



Capacity

1350 Litres

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises

efficient operation even when shelves are fully loaded

- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

Supplied as Standard Optional Not Available Yes No

External Finish

304 Stainless Steel

Stainless Steel

304 Stainless Steel Rear For Island Siting

Internal Finish

304 Stainless Steel

Aluminium

Shelving

Nylon Coated Gastronorm 2/1 Shelf Quantity: 6

Additional Shelf

Doors

Solid Full

Solid Half

Pass Through

Glass with Lights

Base Fittings

80mm Castors

150mm Legs

Refrigeration

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input checked="" type="radio"/>
R404a	<input type="radio"/>
R134a	<input checked="" type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

Electrical Data

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input checked="" type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R290a)	<input type="radio"/>
kW per 24 hr (R134a)	<input type="radio"/>
Test Standard	EN441
Source	ECA test
Amps	<input type="radio"/>
Watts	<input type="radio"/>
Fuse Required	13 amp

Foot Notes

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- Hydrocarbon option not available on glass door models
- 32 C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.

- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

Contact

Foster Refrigerator

Oldmedow Road
King's Lynn
Norfolk
PE30 4JU
United Kingdom

Telephone: **0843 216 8800**
Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE



Authorised User No. 00101