

PT 8301
PT 8303

Products

12-15 Kg Tumble Dryers

Key Features

Powerplus: A performance that offers more, higher air throughput and intelligent air flow for fast drying. Powerful electric and gas heating.

Formplus: A concept that leaves a lasting impression, from product design to enhanced ergonomics and handling.

Flexplus: Profitronic B Plus Controls with 10 moisture controlled and 2 time controlled programmes plus 'Low temperature' function covers the range of moisture controlled applications. Profitronic B Control features timed drying.

Volumeplus: A capacity that defines its size. With a slim build and huge performance.

Ecoplus: A sustainable, cost-effective performance, achieving optimum results. Robust design using recyclable materials for maximum sustainability.

PT 8301



PT 8303



Design

Frontloader, door opening [Ø mm]

520

520

Suitable for stacking

-

-

Drying system

Vented

x

x

Air inlet and exhaust outlet diameter [mm]

DN 150

DN 150

Capacity

Max. load 1:25 - 1:20 [kg]

12 - 15

12 - 15

Drum volume [litres]

300

300

Controls

PROFITRONIC B

x

-

PROFITRONIC B Plus

-

x

Slot for communication module

-

-

* Electro zinc plated x Standard feature o Optional feature - Feature not available

Products

12-15 Kg Tumble Dryers

	PT 8301	PT 8303
Connection options		
Communication module with serial interface	-	-
Payment system	o	o
Peak load cut-out	-	-
Heating		
Electric (EL), Gas (G), Steam (D)	EL/G	EL/G
Electrical connection (electric heating)		
3N AC 380-415 V 50 Hz	14.2 kW/3 x 25 A	14.2 kW/3 x 35 A
3 AC 440 V 60 Hz	-	-
Electrical connection (gas heating)		
1N AC 220-240 V 50 Hz	0.7 kW/1 x 10 A	0.7 kW/1 x 10 A
3N AC 380-415 V 50 Hz	-	-
Dimensions, weight (electric heating)		
External dimensions H/W/D [mm]	1800/7116/1089	1800/7116/1089
Net weight [kg] EL/GAS	139/145	139/145
External finish		
Front, sides and lid octoblue, rear panel*	x	x
Front and lid octoblue, sides and rear panel*	o	o
Sound levels (IEC 704-1 and 704-2-4)	68.9 dB (A)	68.9 dB (A)
Floor load		
Maximum floor load in operation (EL/G)	1584 N/1643 N	1584 N/1643 N
Frequency	-	-

* Electro zinc plated x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

