

PW 6080 Vario
 PWT 6089 Vario
 PW 5105 Vario
 PW 6107

Products

8-10 Kg Washer-Extractors

Key Features

Powerplus: A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.

Careplus: The patented honeycomb drum ensures laundry is cared for. The profiled pattern on the drum creates a protective film of water on which clothing gently slides.

Flexplus: Profitronic L Vario controls - Electronic controls with multi-function selector and user navigation screen. Programme delay and time left display to enable the user to manage their time efficiently. Wide range of standard programmes as well as a number of special programmes such as table linen, pillows and outerwear & reproofing.

Profitronic M controls: Freely programmable. Standard programme packages and a total of 199 programme slots. The temperatures, holding times, wash times, drum rhythms, spin speeds and dosing are all programmable to suit your needs.

Ecoplus: A sustainable, cost-effective performance, achieving optimum results using as little water, energy and detergent as necessary. Robust design using recyclable materials for maximum sustainability.

Comfortplus: A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

	PW 6080 Vario	PWT 6089 Vario		PW 5105 Vario	PW 6107
					
Design		Washer	Dryer		
Door opening Frontloader: [Ø mm]	370	370	440	370	370
Capacity					
Max. load [kg] (based on 1:10 for washer & 1:22.5 for dryer)	8	8	8	10	10
Honeycomb drum volume [litres]	80	80	180	100	100
Moisture control					
Spin speed [max. rpm]	1300	1300	-	1100	1200
g factor	520	520	-	370	475
Residual moisture %	49	49	-	50	47
Controls					
PROFITRONIC L Vario	x	x	x	x	-
PROFITRONIC M					x
Slot for communication module	x	x	x	x	x
Dispenser systems					
4 compartment dispenser in machine front	-	-	-	-	x
3 compartment dispenser in machine front	x	x	-	x	-

*Electro-zinc plated x Standard feature o Optional feature - Feature not available

Products

8-10 Kg Washer-Extractors

	PW 6080 Vario	PWT 6089 Vario	PW 5105 Vario	PW 6107	
Connection options		Washer	Dryer		
External liquid dispensing interface	x	x	-	x	o
Communication module with serial interface	o	o	o	o	o
Payment system	o	o	o	o	o
Plumbing					
1 x Cold water 1/2" with 3/4" threaded union	x	x	-	x	-
2 x Cold water 1/2" with 3/4" threaded union	-	-	-	-	x
1 x Hot water, 1/2" with 3/4" threaded union	x	x	-	x	x
Grey water connection, pre-fitted	x	x	-	x	-
Min. flow pressure 100 kPa (1 bar)	x	x	-	x	x
Max. flow pressure 1000 kPa (10 bar)	x	x	-	x	x
Drain pump DN 22	x	x	-	x	-
Dump valve DN 70	x	x	-	x	x
Drying system					
Vented	-	-	x	-	-
Exhaust diameter [mm]	-	-	100	-	-
Heating					
Electric (EL), Gas (G), Steam (D)	EL	EL	EL	EL	EL/G/D
Electrical connection (electric heating)					
1N AC 220-240 V 50 Hz with cable	5.5 kW / 1 x 25 A	5.5 kW / 1 x 25 A	5.79 kW / 1 x 25 A	5.5 kW / 1 x 25 A	-
3N AC 400 V 50 Hz with cable	8.2 kW / 3 x 16 A	8.2 kW / 3 x 16 A	8.5 kW / 3 x 16 A	8.2 kW / 3 x 16 A	-
3N AC 380-415V 50-60Hz	-	-	-	-	11 kW / 3 x 16 A
3 AC 440V 60 Hz	7.9 kW / 3x16 A	8.2 kW / 3 x 16 A	8.5 kW / 3 x 16 A	7.9 kW / 3x16 A	11 kW / 3 x 16 A
Electrical connection (gas heating)					
3N AC 380-415V 50-60 Hz	-	-	-	-	2.3. kW / 3 x 16 A
Electrical connection (steam heating)					
3N AC 380-415V 50-60 Hz	-	-	-	-	2.3. kW / 3 x 16 A
Dimensions, weight (electric heating)					
External dimensions H/W/D [mm]	1020/700/727	1920/692/763	1920/692/764	1020/700/827	1250/804/925
Net weight [kg]	140	240	180	148	324
External finish					
Front, sides and lid octoblu, rear panel*	x	x	x	x	x
Front and lid stainless steel, sides octoblu, rear panel*	o	o	o	-	o
Sound levels (IEC 704-1 and 704-2-4)					
Wash	54.4 dB	TBA	TBA	TBA	64 (dB re 1pW)
Spin	76.5 dB (A)			73.1 dB (A)	76.6 (dB re 1pW)
Floor load					
Maximum floor load in operation	2600 N	TBA	TBA	2750 N	3970 N
Frequency	TBA	TBA	TBA	18 Hz	20 Hz

*Electro-zinc plated x Standard feature
o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

