



Demand more. Choose Foster

# EP1440L

## EcoPro G2 1350 Litre Upright Freezer Cabinet



### Temperature


---



Freezer  
-18/-21 C

### Dimensions (mm)

---



### Capacity

---

1350 Litres

### Features & Benefits

---

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded

- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

☒ Supplied as Standard
 ☐ Optional
 ☐ Not Available
 ☒ Yes
 ☒ No

### External Finish

---

304 Stainless Steel ☐  
 Stainless Steel ☒  
 304 Stainless Steel Rear For Island Siting ☐

### Internal Finish

---

304 Stainless Steel ☐  
 Aluminium ☒

### Shelving

---

Nylon Coated Gastronorm 2/1 Shelf ☒ Quantity: 6  
 Additional Shelf ☐

### Doors

---

Solid Full ☒  
 Solid Half ☐  
 Pass Through ☐  
 Glass with Lights ☐

### Base Fittings

---

80mm Castors ☒  
 150mm Legs ☐

### Refrigeration

---

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input checked="" type="radio"/>
R404a	<input checked="" type="radio"/>
R134a	<input type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

## Electrical Data

---

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input checked="" type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R290a)	<input type="radio"/>
kW per 24 hr (R404a)	<input type="radio"/>
Test Standard	<b>EN441</b>
Source	<b>ECA test</b>
Amps	<input type="radio"/>
Watts	<input type="radio"/>
Fuse Required	<b>10 amp</b>

## Foot Notes

---

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- Hydrocarbon option not available on glass door models
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.
- Depth with door open is 1500mm

- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

## Contact

---

### Foster Refrigerator

Oldmedow Road  
King's Lynn  
Norfolk  
PE30 4JU  
United Kingdom

Telephone: **0843 216 8800**  
Facsimile: **0843 216 4700**

[sales@foster-uk.com](mailto:sales@foster-uk.com)



**GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE**



Authorised User No. 00101