

Demand more. Choose Foster

EP700HU

EcoPro G2 600 Litre Upright Undermount Refrigerated Cabinet







Dimensions (mm)



Capacity

600 Litres

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- Provides an alternative format for high ambients as it takes cooler air from floor level
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning

 Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded 					
 Brand-new refrigeration system de and energy efficient yet 	signed to be the most technolo	ogically advanced			
Supplied as Standard Opt	ional O Not Available				
External Finish					
304 Stainless Steel	•				
Stainless Steel					
304 Stainless Steel Rear For Island Siting	•				
Internal Finish					
004.00					
304 Stainless Steel	0				
Aluminium					
Shelving					
Additional Shelf	•				
Nylon Coated Gastronorm 2/1 Shelf	Quantity: 3				
Doors					
Solid Full	•				
Solid Half	0				
Hinged - Right Hand					
Hinged - Left Hand	0				
Pass Through	0				
Glass with Lights	0				
Base Fittings	S				

80mm Castors	•	
150mm Legs	①	
Roller Castors	•	
Refrigeration		
Forced Air	•	
Integral	•	
R290 (Hydrocarbon)	①	
R404a	①	
R134a		
Thermal Heat Rejection (Kw/24hrs)	0	
Noise DBA	0	
Drain Required?	N	
Electrical Data		
230 Volts		
50Hz		
60Hz	•	
1 Phase	•	
kW per 24 hr (R290a)	0	
kW per 24 hr (R134a)	0	
Test Standard	EN441	
Source	ECA test	
Amps	0	
Watts	0	
Fuse Required	10 amp	
Foot Notes		

- Optional castors supplied as standard increase overall height to 2070mm
- 150mm castors are not available if product is supplied less condensing unit

- Adequate airflow and service space must be kept above the top of cabinet: 150mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- Marine kit option includes legs, bulkhead brackets & marine shelves.

Contact

Foster Refrigerator

Oldmedow Road King's Lynn Norfolk PE30 4JU United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE

