



Demand more. Choose Foster

# EP700LU

## EcoPro G2 600 Litre Upright Undermount Freezer Cabinet



### Temperature


---



Freezer  
-18/-21 C

### Dimensions (mm)

---



### Capacity

---

600 Litres

### Features & Benefits

---

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- Provides an alternative format for high ambients as it takes cooler air from floor level
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning

- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

Supplied as Standard    
  Optional    
  Not Available    
  Yes    
  No

### External Finish

---

304 Stainless Steel 
  
 Stainless Steel 
  
 304 Stainless Steel Rear For Island Siting

### Internal Finish

---

304 Stainless Steel 
  
 Aluminium

### Shelving

---

Nylon Coated Gastronorm 2/1 Shelf  Quantity: **2**
  
 Additional Shelf

### Doors

---

Solid Full 
  
 Solid Half 
  
 Hinged - Right Hand 
  
 Hinged - Left Hand 
  
 Pass Through 
  
 Glass with Lights

### Base Fittings

---

80mm Castors	<input checked="" type="radio"/>
150mm Legs	<input checked="" type="radio"/>
Roller Castors	<input checked="" type="radio"/>

## Refrigeration

---

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input type="radio"/>
R404a	<input checked="" type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

## Electrical Data

---

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input checked="" type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R404a)	<input type="radio"/>
Test Standard	<b>EN441</b>
Source	<b>ECA test</b>
Amps	<input type="radio"/>
Watts	<input type="radio"/>
Fuse Required	<b>10 amp</b>

## Foot Notes

---

- Optional castors supplied as standard increase overall height to 2070mm
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 150mm.

- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- Marine kit option includes legs, bulkhead brackets & marine shelves.

## Contact

---

### Foster Refrigerator

Oldmedow Road  
King's Lynn  
Norfolk  
PE30 4JU  
United Kingdom

Telephone: **0843 216 8800**  
Facsimile: **0843 216 4700**

[sales@foster-uk.com](mailto:sales@foster-uk.com)



**GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE**



Authorised User No. 00101