



Demand more. Choose Foster

EP820LU

EcoPro G2 600 Litre Broadway Upright Undermount Freezer Cabinet




Temperature



Freezer
-18/-21 C

Dimensions (mm)



Capacity

600 Litres

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- Provides an alternative format for high ambients as it takes cooler air from floor level
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning

- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

☒ Supplied as Standard
 ☐ Optional
 ☐ Not Available
 ☒ Yes
 ☒ No

External Finish

304 Stainless Steel ☐
 Stainless Steel ☒
 304 Stainless Steel Rear For Island Siting ☐

Internal Finish

304 Stainless Steel ☐
 Aluminium ☒

Shelving

Nylon Coated Gastronorm 2/1 Shelf ☒ Quantity: **3**
 Additional Shelf ☐

Doors

Solid Full ☒
 Hinged - Right Hand ☒
 Hinged - Left Hand ☐

Base Fittings

80mm Castors ☐
 150mm Legs ☐
 Roller Castors ☒

Refrigeration

Electrical Data

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R290a)	<input type="radio"/>
kW per 24 hr (R404a)	<input type="radio"/>
Test Standard	EN441
Source	ECA test
Amps	<input type="radio"/>
Watts	<input type="radio"/>
Fuse Required	13 amp

Foot Notes

- Optional castors supplied as standard increase overall height to 2070mm
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 150mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- Marine kit option includes legs, bulkhead brackets & marine shelves.

Contact

Foster Refrigerator

Oldmedow Road
King's Lynn
Norfolk
PE30 4JU
United Kingdom

Telephone: **0843 216 8800**
Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE



Authorised User No. 00101