

Demand more. Choose Foster

HR150

HR150 Refrigerated Undercounter Cabinet



Temperature

| Refrigerator 3/5 C | | | |
|-----------------------|--|--|--|
| Dimensions (mm) | | | |
| w 605 D 640 н 830 | | | |
| Capacity | | | |
| 153 Litres | | | |

Features & Benefits

Undercounter refrigeration ensures optimum use of space in tight kitchen areas, and none more so than Foster's high performance, low cost range of undercounter cabinets

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Door lock for security

| \odot | Supplied as Standard | | Optional | 0 | Not Available | \otimes | Yes | N | No |
|---------|----------------------|--|----------|---|---------------|-----------|-----|---|----|
|---------|----------------------|--|----------|---|---------------|-----------|-----|---|----|

External Finish

| Stainless Steel | |
|-----------------------------------|-------------|
| Internal Finish | |
| | |
| Aluminium | ۲ |
| Shelving | |
| Additional Shelf | |
| Nylon Coated Shelf | Quantity: 2 |
| Uprights and Shelf Retainer | |
| | |
| Worktop & Drawers | |
| 1/3 Drawers | |
| Doors | |
| | |
| Solid Full | |
| Hinged - Right Hand | |
| Hinged - Left Hand | |
| Base Fittings | |
| Rear Fixed Castors | ۲ |
| Levelling Bolts | |
| Refrigeration | |
| | |
| Forced Air | ۲ |
| Integral | |
| R290 (Hydrocarbon) | |
| R134a | |
| Thermal Heat Rejection (Kw/24hrs) | 0 |
| | |

| Noise DBA | 0 |
|----------------------|--------------------|
| Drain Required? | N |
| Electrical Data | |
| | |
| 230 Volts | |
| 50Hz | ۲ |
| 1 Phase | ۲ |
| kW per 24 hr (R134a) | 1.4 |
| Test Standard | PR EN153 |
| Source | Laboratory Test |
| Watts | 0 |
| Fuse Required | 13 amp |
| Product Extras | |
| | |
| Helicoil Mains Lead | |
| Foot Notes | |

- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Meets ISO Climate Class 4 up to 32'C Ambient, Glass door models 25'C Ambient
- Hydrocarbon not available on glass door option
- Decibel rating measured 1m high from the floor and 1m from the cabinet

Contact

Foster Refrigerator

Oldmedow Road King's Lynn Norfolk PE30 4JU United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE