## **WTpes 5972**

## Vinidor





Model classification		
Energy consump. in 365 days/24 h Gross/net capacity Total gross/net capacity  Total gross/net capacity  Max. No. of Bordeaux bottles 0.75 Ltr Climate rating³ Noise level 38 dB(A) Voltage 220-240 V ~ Connection Rating 1.0 A Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones Temperature range 4-5°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Forced air system Defrosting Interior light LED permanently activated/dimmable with integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Peatures Interiae HomeDialog Design HardLine Shelf material Scorage shelves Full-out shelves on telescopic rails Activated charcoal filter yes right, reversible	Model classification <sup>1</sup>	2
Energy consump. in 365 days/24 h Gross/net capacity Total gross/net capacity Max. No. of Bordeaux bottles 0.75 Ltr Climate rating³ SN-ST Noise level Voltage 220-240 V ~ Connection Rating 1.0 A Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones Temperature zones 12 Type of Control LC-Display Temperature display Forced air system Defrosting Interior light Permanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Dimensions Height Width 70 cm Depth incl. distance from wall Peatures Interior light Voes Peatures Interdiace HomeDialog Design HardLine Shelf material Scorage shelves Full-out shelves on telescopic rails Activated charcoal filter Ves Interversible	Energy efficiency class	B
Gross/net capacity Total gross/net capacity Max. No. of Bordeaux bottles 0.75 Ltr Climate rating³ SN-ST Noise level 38 dB(A) Voltage 220-240 V ~ Connection Rating 1.0 A Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones Temperature range 4-5°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Internal digital Forced air system Defrosting Interior light LED permanently activated/dimmable with integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interiae HomeDialog Design HardLine Shelf material Scorage shelves Full-out shelves on telescopic rails Activated charcoal filter yes right, reversible		248/0,679 kWh
Total gross/net capacity  Max. No. of Bordeaux bottles 0.75 Ltr Climate rating³  Noise level  Voltage  220-240 V ~  Connection Rating  1.0 A  Door  Insulated glazed door, S/Steel frame Side walls  Wine storage compartment  Temperature zones  2  Temperature range  45°C to +20°C  Adjustable cooling circuits  2  Type of Control  Temperature display  Forced air system  Defrosting  Interior light  LED  permanently activated/dimmable Handle  with integrated opening mechanism  Child proof function  Fault: warning signal  Door open: warning signal  Dimensions  Height  192 cm  Width  70 cm  Depth incl. distance from wall  Storage shelves  Pull-out shelves on telescopic rails  Activated charcoal filter  yes  poor hinges  Fight, reversible		,
Max. No. of Bordeaux bottles 0.75 Ltr Climate rating³ Noise level Voltage 220-240 V ~ Connection Rating 1.0 A Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones 2 Temperature range 45°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Forced air system Defrosting Interior light LED permanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Ves Ves Pull-out shelves on telescopic rails Activated charcoal filter Ves Ves Poor hinges Ves Poor pingt, reversible		593/528 litre
Noise level Voltage Voltage Connection Rating Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones Temperature range Adjustable cooling circuits Type of Control LC-Display Temperature display Internal digital Forced air system Defrosting Interior light Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Door open: warning signal Height Teatures Interface Design HardLine Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Ves - 220°C Adjustable cooling circuits 2 Type of Control LC-Display Internal digital Por C Peatures Interface HomeDialog Dimensions Height 192 cm Visual and audible	. ,	155
Noise level Voltage Voltage Connection Rating Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones Temperature range Adjustable cooling circuits Type of Control LC-Display Temperature display Internal digital Forced air system Defrosting Interior light Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Door open: warning signal Height Teatures Interface Design HardLine Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Ves - 220°C Adjustable cooling circuits 2 Type of Control LC-Display Internal digital Por C Peatures Interface HomeDialog Dimensions Height 192 cm Visual and audible	Climate rating <sup>3</sup>	SN-ST
Voltage Connection Rating Door Insulated glazed door, S/Steel frame Side walls  Wine storage compartment Temperature zones 2 Temperature range Adjustable cooling circuits 2 Type of Control Temperature display Forced air system Defrosting Interior light LED permanently activated/dimmable with integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges Insulazed door, S/Steel frame 1.0 A Insulated glazed door, S/Steel frame Stainless steel  1.0 A Insulated glazed door, S/Steel frame Stainless steel  1.0 A Insulated glazed door, S/Steel frame Stainless steel  1.0 A Insulated glazed door, S/Steel frame Stainless steel  2  Child pro°C Systeel slimine Internal digital Fest yes Jess ye		38 dB(A)
Connection Rating Door Insulated glazed door, S/Steel frame Side walls stainless steel  Wine storage compartment Temperature zones 2 Temperature range +5°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display internal digital Forced air system yes Defrosting automatic Interior light LED permanently activated/dimmable yes / yes Handle S/Steel slimline door handle with integrated opening mechanism Child proof function yes Fault: warning signal visual and audible Door open: warning signal audible  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails Activated charcoal filter yes Door hinges right, reversible	Voltage	` '
Door Side walls Side walls Stainless steel  Wine storage compartment Temperature zones 2 Temperature range +5°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Forced air system Defrosting LED permanently activated/dimmable Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Depth incl. distance from wall  Features Interface Design HardLine Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges right, reversible		1.0 A
Wine storage compartment Temperature zones 2 Temperature range +5°C to +20°C Adjustable cooling circuits 2 Type of Control LC-Display Temperature display internal digital Forced air system yes Defrosting automatic Interior light LED permanently activated/dimmable yes / yes Handle S/Steel slimline door handle with integrated opening mechanism Child proof function yes Fault: warning signal visual and audible Door open: warning signal audible  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails Activated charcoal filter yes Door hinges right, reversible		Insulated glazed door, S/Steel frame
Temperature zones Temperature range Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Forced air system Defrosting Interior light permanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Dimensions Height Dimensions Height Dimensions Height Dimensions Height Dimensions Height Additional opening Depth incl. distance from wall  Features Interface Design HardLine Shelf material Storage shelves Door hinges Fight, reversible	Side walls	
Temperature zones Temperature range Adjustable cooling circuits 2 Type of Control LC-Display Temperature display Forced air system Defrosting Interior light permanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal Dimensions Height Dimensions Height Peatures Interface Design HardLine Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Display Interface LC-Display Internal digital  2 T.C-Display Internal digital  3 Internal digital  4 Internal digital  5 Internal digital  8 Internal digital  9 Internal		
Temperature range	Wine storage compartment	
Adjustable cooling circuits  Type of Control  Temperature display  Forced air system  Defrosting  Interior light  permanently activated/dimmable  with integrated opening mechanism  Child proof function  Fault: warning signal  Door open: warning signal  Dimensions  Height  192 cm  Width  70 cm  Depth incl. distance from wall  Features  Interface  Design  Shelf material  Storage shelves  Pull-out shelves on telescopic rails  Activated charcoal filter  Door hinges  Interrace  Door hinges  LC-Display  internal digital  2  LC-Display  internal digital  2  LC-Display  internal digital  2  LED  yes /yes /yes /yes  Jest of Control  LED  yes /yes /yes  Jest of Control  LED  yes /yes /yes /yes /yes /yes /yes /yes	Temperature zones	2
Type of Control Temperature display Forced air system Defrosting Interior light permanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door opening mechanism  LED yes yes  yes  yes  yes  yes  yes  192 cm  Width 70 cm  74,2 cm	Temperature range	+5°C to +20°C
Temperature display Forced air system Defrosting Interior light Defrosting Interior light Demanently activated/dimmable With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Design Interface Door hinges Interrow Interval digital  yes  unternal digital  internal digital  pes  yes    June   June	Adjustable cooling circuits	2
Forced air system Defrosting Interior light permanently activated/dimmable Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height Width 70 cm Depth incl. distance from wall  Features Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges  LED  yes  Attivated charcoal filter  yes  yes  yes  yes  yes  yes  yes  y		LC-Display
Defrosting Interior light permanently activated/dimmable Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height Width To cm Depth incl. distance from wall  Features Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Dimensions  automatic LED yes / yes // yes /	Temperature display	internal digital
Interior light permanently activated/dimmable Handle With integrated opening mechanism Child proof function Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Dives / yes  // yes	Forced air system	yes
permanently activated/dimmable yes / yes Handle S/Steel slimline door handle with integrated opening mechanism Child proof function yes Fault: warning signal visual and audible Door open: warning signal audible  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails Activated charcoal filter yes Door hinges right, reversible	Defrosting	automatic
Handle S/Steel slimline door handle with integrated opening mechanism Child proof function yes Fault: warning signal visual and audible Door open: warning signal audible  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails Activated charcoal filter yes Door hinges right, reversible	Interior light	LED
with integrated opening mechanism Child proof function yes Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface HomeDialog Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges  Visual and audible  Visual and audible  Width 40 cm  HomeDialog  HardLine 5 code of the shelf 5 code of the shelf 5 code of the shelf 9 cm  Visual and audible  Visual and audible  Visual and audible  Nome  Visual and audible  HomeDialog  Form  Features  Interface Form Form Form Form Form Form Form Form	permanently activated/dimmable	yes / yes
Child proof function Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface Design HardLine Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges Visual and audible  Nesula audible  HomeDialog HardLine  HomeDialog HardLine Shelf material Storage shelves Features Features Features Interface HomeDialog Features Forage shelves Forage shel	Handle	S/Steel slimline door handle
Fault: warning signal Door open: warning signal  Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall  Features Interface Interface Design Shelf material Storage shelves Pull-out shelves on telescopic rails Activated charcoal filter Door hinges  visual and audible	with integrated opening mechanism	_
Door open: warning signal audible  Dimensions  Height 192 cm  Width 70 cm  Depth incl. distance from wall 74,2 cm  Features  Interface HomeDialog  Design HardLine  Shelf material wooden shelf  Storage shelves 6  Pull-out shelves on telescopic rails 5  Activated charcoal filter yes  Door hinges right, reversible	Child proof function	yes
Dimensions Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible	Fault: warning signal	visual and audible
Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible	Door open: warning signal	audible
Height 192 cm Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible		
Width 70 cm Depth incl. distance from wall 74,2 cm  Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible	Dimensions	
Depth incl. distance from wall  74,2 cm  Features  Interface Design HardLine Shelf material Wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails Activated charcoal filter Door hinges  74,2 cm  HomeDialog Wooden shelf 5 For a shelf Storage shelves 6 Pull-out shelves on telescopic rails 74,2 cm	Height	192 cm
Features Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible		70 cm
Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible	Depth incl. distance from wall	74,2 cm
Interface HomeDialog Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible		
Design HardLine Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible	Features	
Shelf material wooden shelf Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible		S .
Storage shelves 6 Pull-out shelves on telescopic rails 5 Activated charcoal filter yes Door hinges right, reversible		
Pull-out shelves on telescopic rails Activated charcoal filter Door hinges  5 yes right, reversible		wooden shelf
Activated charcoal filter yes Door hinges right, reversible	-	
Door hinges right, reversible	·	
		•
EAN-Nr. 9005382146637		-
	EAN-Nr.	9005382146637

- 1 Model classification: 2 Appliances with cooling- und cellar-box
- 2 \*\*\*\* freezer compartment with -18 °C or colder
- 3 Climate Ratings: SN +10°C to +32°C N +16°C to +32°C ST +16°C to +38°C T +16°C to +43°C
- 4 Fixed water connection 3/4" and solenoid valve (needs to be plumped in)
- 5 To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. These increase the appliance depth by approximately 3.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.