

## Products

# 16-20 Kg Tumble Dryers

### Key Features



**Powerplus:** A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.

**Careplus:** The patented honeycomb drum ensures laundry is cared for - air pockets provide cushion protection and reduce fibre wear. SoftLift ribs ensure traction is increased, this ensures that the laundry travels further and has extended exposure to the heated air flow.

**Flexplus:** Profitronic M controls - Freely programmable. Standard programme packages and a total of 199 programme slots. The graphic display combines symbols and text for easy programming and programmes are selected via a rotary dial. The temperatures, holding times, wash times, drum rhythms, spin speeds and dosing are all programmable to suit your needs. Profitronic B Plus Controls are with 10 moisture controlled and 2 time controlled programmes as well as the "Low temperature" function covers the range of moisture controlled applications

**Ecoplus:** A sustainable, cost-effective performance, achieving optimum results. Robust design using recyclable materials for sustainability. Hot air recycling combined with a reverse action drum to ensure maximum energy efficiency.

**Comfortplus:** A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

	PT 8403	PT 8407
		
<b>Design</b>		
Frontloader, door opening [Ø mm]	520	520
Suitable for stacking	-	-
<b>Drying system</b>		
Vented with AirRecycling system	x	x
Air inlet and exhaust outlet diameter [mm]	DN 150	DN 150
<b>Capacity</b>		
Max. load 1:25 - 1:20 [kg]	16 - 20	16 - 20
Patented Honeycomb drum volume [litres]	400	400
<b>Controls</b>		
PROFITRONIC M	-	x
PROFITRONIC B PLUS	x	-
Slot for communication module	x	x

\*Electro zinc plated   x Standard feature   o Optional feature   - Feature not available

## Products

# 16-20 Kg Tumble Dryers

PT 8403

PT 8407

### Connection options

Communication module with serial interface	o	o
Payment system	-	-
Peak load cut-out	o	o

### Heating

Electric (EL), Gas (G), Steam (D)	EL/G/D	EL/G/D
-----------------------------------	--------	--------

### Electrical connection

(electric heating)

3N AC 380 - 415 V 50 Hz	23.8 kW/3 x 50 A	-
3 AC 220 - 240 V 50 Hz	-	23.8 kW/3 x 63 A
3 AC 440 V 60 Hz	14.3 kW/3 x 25 A	23.8 kW/3 x 35 A

### Electrical connection

(gas heating)

1N AC 220-240 V 50 Hz	-	-
3N AC 380-415 V 50 Hz	1.3kW/3 x 10 A	1.3 kW/3 x 10 A

### Dimensions, weight

(electric heating)

External dimensions H/W/D [mm]	1400/906/1148	1400/906/1148
Net weight [kg]	191	191

### External finish

Front, sides and lid octoblué, rear panel*	x	x
Front stainless steel, lid & sides octoblué, rear panel*	o	o

### Sound levels

(IEC 704-1 and 704-2-4)

72.8 dB (A)	TBA
-------------	-----

### Floor load

Maximum floor load in operation (EL/G)	2163 N/2143 N	TBA
Maximum floor load in operation (STEAM)	2408 N	TBA
Frequency	-	-

\*Electro zinc plated x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

