

PT 5137 WP
PT 7135 C Vario
PT 7136 Vario

Products

Little Giant Tumble Dryers

Key Features

Powerplus: A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.

Careplus: The patented honeycomb drum ensures laundry is cared for - air pockets provide cushion protection and reduce fibre wear. SoftLift ribs ensure traction is increased, this ensures that the laundry travels further and has extended exposure to the heated air flow.

Flexplus: Profitronic L Vario controls - Electronic controls with multi-function selector and user navigation screen. Programme delay and time left display to enable the user to manage their time efficiently. Wide range of standard programmes as well as a number of special programmes such as table linen, pillows and outerwear & reproofing. Profitronic B Plus controls are with 10 fixed and 2 time controlled programmes as well as the "Low temperature" function to cover the range of moisture controlled applications.

Ecoplus: A sustainable, cost-effective performance, achieving optimum results by utilising sensitive electronic moisture control and a reversing drum action. Robust design using recyclable materials for maximum sustainability.

Comfortplus: A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

	PT 5137 WP	PT 7135 C Vario	PT 7136 Vario
			
Design			
Frontloader, door opening [Ø mm]	300	300	300
Suitable for stacking	x	x	x
Drying system			
Heat pump	x	-	-
Condenser	-	x	-
Vented	-	-	x
Exhaust diameter [mm]	-	-	100
Capacity			
Max. load [kg]	See footnote	See footnote	See footnote
Patented Honeycomb drum volume [litres]	6.5 ¹	6.5 ¹	6.5 ¹
	130	130	130

¹ 1:25 [kg] x Standard feature o Optional feature - Feature not available

Little Giant Tumble Dryers

	PT 5137 WP	PT 7135 C Vario	PT 7136 Vario
Controls			
PROFILINE B Plus	x	-	-
PROFITRONIC L Vario	-	x	x
Connection options			
Payment system	o	o	o
Heating			
Electric (EL), Gas (G), Steam (D)	EL	EL	EL
Electrical connection (electric heating)			
1N AC 220-240 V 50 Hz with cable and plug	1.25 kW/1 x 10A	2.95 kW/1 x 13 A	2.95 kW/1 x 13 A
1N AC 220-240 V 50 Hz with cable	-	-	5.52 kW/1 x 25 A
3N AC 400 V 50 Hz with cable	-	-	6.44 kW/3 x 10 A
3 AC 440 V 60 Hz	-	-	6.44 kW/3 x 10 A
Electrical connection (gas heating)			
1N AC 220-240 V 50 Hz	-	-	-
3N AC 380-415 V 50 Hz	-	-	-
Dimensions, weight (electric heating)			
External dimensions H/W/D [mm]	850/595/700	850/595/700	850/595/700
Net weight [kg]	77	60.5	57.5
External finish			
Front and sides white, fascia and lid stainless steel	x	x	x
Front, sides and lid stainless steel	-	o	o
Sound levels (IEC 704-1 and 704-2-4)			
	TBA	68 dB re 1pW	65 dB re 1pW
Floor load			
Maximum floor load in operation	TBA	680 N	680 N
Frequency	-	-	-

1 1:25 [kg] 2 1:25 - 1:20 x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

